

PRODUCT HIGHLIGHTS

4063-F

Super Stick Trim Adhesive (50 State)

DESCRIPTION:

Super Stick Trim Adhesive is a non-staining, fast drying, high strength material. For best results, use at room temperature. This product is 50 state compliant and meets all regulations for sale in the USA. Meets CARB/OTC V.O.C. limit with less than 55% V.O.C by weight.

PRODUCTS:

4063-F Super Stick Trim Adhesive (50 State), 24 oz. aerosol (710 ml), 6/case



SURFACE PREP:

Clean with SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394.



MIX RATIO:

Ready to spray.



FLASH TIME:

1 - 3 minutes

*See next page for more detailed product application. See website for this document in other languages.
Vea la página siguiente para un uso más detallado del producto. Vea el Web site para este documento en español.
Voir la prochaine page pour une application plus détaillée de produit. Voir le site Web pour ce document en français.*

PRODUCT DATA

4063-F

Super Stick Trim Adhesive (50 State)

SUITABLE SUBSTRATES:

Carpets, trunk linings, trim fabrics (except vinyl and silencer pads).

SURFACE PREPARATION:

Wash and solvent clean to remove all road dirt, grease and silicone. Use SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394.

APPLICATION:

The methylene chloride free formula bonds carpets, trunk linings, trim fabrics (except vinyl) and silencer pads. Super Stick Trim Adhesive can also be used as a good general purpose rubber cement.



1. Shake well.

2. Wash and solvent clean to remove all road dirt, grease and silicone. Use SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394.

3. Select desired spray pattern by turning activator button. Hold can 6 - 10 inches from surface, apply a uniform overlap coat to both bonding surfaces.

4. Allow to flash for 1 - 3 minutes until tacky, then press firmly together.

CAUTION: Since solvent may mar or attack some plastic or painted surfaces, masking is required where overspray may occur. This product is not recommended for installation of complete or partial vinyl tops. It may be used for small repair jobs on vinyl tops.

TECHNICAL DATA:

APPEARANCE: Opaque

SHELF LIFE: 1 year unopened

ADVANTAGES:

- Fast drying
- High strength
- 50 State Compliant
- Methylene chloride free formula
- Adjustable spray nozzle
- Convenient aerosol

COMPETITION:

3M 08090 Wurth 890100055 Kent 10522 Dominion SS 24059 Rubberseal RS580 Marhyde 3411

REGULATORY:

Category: Web Spray Adhesive 4063-F	Individual Component
VOC Content	<55%

See website (www.tat-co.com) for this document in other languages.

Vea el Web site (www.tat-co.com) para este documento en español.

Voir le site Web (www.tat-co.com) pour ce document en français.