



PRODUCT DATA

4136

Kwik-On Body Seam Tape

DESCRIPTION:

Kwik-On Body Seam Tape is a pressure sensitive, solid translucent acrylic tape to provide superior bond to a wide variety of substrates. Apply to clean, dry oil-free surfaces to provide a seal against air, dust and moisture contamination. Designed to duplicate the factory appearance and function typically found in door jambs, trunk gutters, etc. Can be painted immediately. Tape possesses a high tack acrylic adhesive on one side and the other surface is a specially designed, paintable non-tacky acrylic polymer.

TECHNICAL DATA:

APPEARANCE:	Translucent		
SHELF LIFE:	One year		
TAPE THICKNESS:	0.040"		
TAPE WIDTH:	4136 - 1"		
TENSILE STRENGTH:	200 psi ASTM	D412	Die C
ELONGATION:	500% ASTM	D412	Die C
PEEL ADHESION:	15 pli ASTM	D3330	

APPLICATION INSTRUCTIONS:

1. Make sure all surfaces to be repaired are free of grease, dirt or foreign matter. Use SCAT #6311, Speedi SCAT #6321 Aqua SCAT #6351/6354 to clean surface. Bare metal should be primed using Self Etching Primer 6111/6121, 6183/6184 or Epoxy Primers #6100 Series.
2. If applying to existing OEM finish, clean as above and lightly scuff, clean again and allow to flash dry.
3. Position Kwik-On Body Seam Tape. Remove release paper and press firmly into place. Pre-Clean tape with Acry Solvent #9783/9784 or SCAT #6311 or Speedi SCAT #6321 or Aqua SCAT #6351/6354 prior to painting.

SALES POINTS:

- Easy to apply
- Instant pressure sensitive acrylic tape holds in place firmly
- No shrinkage
- Compresses and forms to difficult shapes
- Paintable immediately
- Excellent moisture resistance
- Faster application than typical seam sealers, no clean up saves time
- Reduces noise and vibration

COMPETITION:

Kent, Tape-A-Seam 40525	Dominion Sure Seal, 3075
IES, Seam Tape 70700,70705	PDQ, Sealer Tape
RBL, 217, 218	3M, 08475, 08476

(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

PACKAGE SIZE:

#4136 Kwik-On Seam Tape, 1"width x 25'/roll, 6/case

