

Technical Data Sheet

Rubberized Undercoat is designed for use on new panel and fender replacements, section repairs, weld joints and rust holes as a sound deadener and rust preventative. Seals out dust fumes, heat and cold. For best results use at room temperature.

SUITABLE SUBSTRATES

Substrate		Substrate		Substrate	
Painted or Primed Steel	✓	Aluminum Wheel Wells	✓	Frame Rails	✓
Bare Steel	✓	Galvanized Steel	✓	Bare Aluminum	✓

MIXING



Mix Ratio: Ready to Spray

Pot Life: N/A

SURFACE PREPARATION



Clean with SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394.

APPLICATION



1. Shake well. Clean surface using SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394.
2. Holding can 8- 10 inches from surface, apply 2- 3 light even coats. Short, even strokes will produce best results.
3. Remove overspray with Acry Solvent 9783/9784.
4. When finished, invert can and spray until valve is free of material to prevent clogging.

IMPORTANT: On cars equipped with catalytic converters, exhaust components operate at temperatures exceeding 1000°F (520°C). Therefore, avoid application of undercoating and/ or rust proofing materials within 12" of the exhaust system.

PRODUCT SPECIFICATIONS

Color: Black	Shelf Life: 1 year
Size: 20 oz Aero	

REGULATORY

Category: Undercoat	4373
VOC Content	<40% by weight

LIMITATIONS & PRECAUTIONS

- This product provides adhesion & corrosion protection when used over noted (checked) substrates - when properly cleaned, sanded & applied.
- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.
- All Standard Operating Procedures (SOP) can be found on the Transtar website at www.tat-co.com.

TRANSTAR AUTOBODY TECHNOLOGIES • 2040 HEISERMAN DRIVE, BRIGHTON, MI 48114 • (800) 824-2843

FAX (800) 477-7923 • EMAIL: info@tat-co.com