

Technical Data Sheet

Ultimate Finish System™ Machine Polish’s advanced technology eliminates 2000 grit or finer imperfections and scratches leaving a high gloss finish. Machine Polish is safe on all paints and is easy to clean. Its increased open time allows you to buff longer using less material for an impeccable shine. For best results, use with Transtar’s Machine Polish Pad 5282.

MIXING



Mix Ratio: Ready to Use
 Pot Life: N/A

SURFACE PREPARATION



Wash surface to be sanded with soap and water.

Sand 1200-2000 grit, wet or dry until imperfections or defects are removed. Finish sand with 1500-2000 grit.

APPLICATION



Do not apply in direct sunlight. Shake container well before use. Apply a 1.25” wide by 6” long ribbon (for every 2’ x 2’ area to polish) of Machine Polish and spread with pad to minimize sling. Using a buffer at low speed (1000 rpm), work material in a circular overlapping motion with Machine Polish White Foam Pad 5282. Make sure to apply sufficient pressure to remove imperfections and scratches. Continue buffing until desired gloss is obtained. Care must be taken to avoid scouring the finish. Finish by removing any polish residue with clean microfiber cloth.

PRODUCT SPECIFICATIONS

Color: White	Shelf Life: 1 year
Size: Quart (5374)	

REGULATORY

VOC Content: <17% by weight	Category: Automotive Rubbing or Polishing Compound
-----------------------------	--

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.