



PRODUCT DATA

6351, 6354 Aqua SCAT Waterborne Degreaser

DESCRIPTION:

Aqua SCAT is a non-hazardous, solvent free cleaner and degreaser for cleaning surfaces prior to applying primer, sealer, basecoat, clearcoat or other coatings. It is intended for use as a final wash for metal, plastics, and coatings. It cleans sanding dust and grime from these substrates. Aqua SCAT works well removing road grime, salt dust, insects, bird droppings, silicone oils, waxes and masking tape residue. When used as directed Aqua SCAT leaves no harmful residue and assists in proper coating adhesion.

TECHNICAL DATA:

APPEARANCE:	Clear liquid
SOLIDS:	<10%
V.O.C. CONTENT:	0.00 #/gal (0g/l)
SHELF LIFE:	One year (unopened)

SUITABLE SUBSTRATES:

Excellent for cleaning sanded old or original finishes and for use on surfaces coated with primer or surfacer which has been subsequently sanded.

- Bare metal
- OEM top coats and primers
- Refinish undercoats and topcoats
- Sanded substrates and primers
- Cured, repainted surfaces
- Cured sealers
- Plastics (PU, TPO, RIM, PPO)

SALES POINTS:

- V.O.C. free
- Replaces hazardous, flammable and unhealthy solvents
- Meets SCAQMD definition as a Clean Air Solvent
- No offensive odors
- Removes many different soils and contaminants
- Easily removes wax and compounding buildup (in door jams, etc.)
- Won't swell or harm plastics

SEE REVERSE SIDE FOR APPLICATION INSTRUCTIONS

(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

PACKAGE SIZES:

- 6351 Aqua SCAT Waterborne Degreaser, Gallon (3.78 L), 4/case
6354 Aqua SCAT Waterborne Degreaser, Quart (0.946 L), 6/case

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.



6351, 6354

Aqua SCAT

Waterborne Degreaser

APPLICATION:

Apply Aqua SCAT to the surface to be cleaned with a fine mist spray bottle or with a liberally wetted clean cloth. Wipe the surface dry with a clean cloth. Repeat the application as necessary. Use of safety glasses and rubber gloves is recommended.

Do not allow Aqua SCAT to dry on the surface since this will leave behind the contaminants you are trying to remove. If drying occurs repeat the application. This product is not recommended for cleaning spray guns or tools.

Note: Do not use 6351/6354 for cleaning glass or clear plastic parts. Remember to remove plastic insert on #6354 quart before using.

COMPETITION:

DuPont, 3909S
Spies Hecker, 7090
Standox, 15889
PPG Deltron, DX394
PPG Specialty, SX1005
ICI, P980-251
Glasurit, 700-1
Lesonal, 072616
Sherwin Williams, W4K 157
Matrix, MXW9001