

Technical Data Sheet

Universal Urethane Activator is a high quality catalyst formulated for use in urethane enamels. It provides a high level of gloss, combined with a hard, durable finish. Universal Urethane Activator is compatible with major paint company urethane paint systems, and will meet or exceed standard performance characteristics.

SURFACE PREPARATION



Refer to topcoat manufacture for surface preparation.

MIXING & APPLICATION

Read all instructions thoroughly. Follow paint manufacturer's directions completely regarding proper techniques for proper mixing and application. DO NOT SPRAY HOT CATALYZED COATINGS. Thoroughly clean equipment after use. Catalyzed material will harden if allowed to remain in gun and cup. Pot life of activated coating will vary depending on shop climate. Refer to paint manufacturer's instructions for exact times.

PRODUCT SPECIFICATIONS

Color: Clear liquid	Shelf Life: 1 year
Size: Quart	% Solids: 43%

REGULATORY

Category: Single Stage Coating	7604	Weight % of Exempt Compounds	0
VOC Actual	4.6#/gal (551 g/l)	Volume % of Exempt Compounds	0
VOC Regulatory	4.6#/gal (551 g/l)	Density of Material #/gal	8.03
Weight % of Volatiles	57.25		
Weight % of Water	0		

LIMITATIONS & PRECAUTIONS

- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.