

# Technical Data Sheet

Low Spot Finder Guide Coat is a specialty coating that will provide the technician with a visual aid to ensure primed surfaces are totally smooth. This product sands easily and will not clog sandpaper. Low Spot Finder Guide Coat is fast drying and ready to sand in minutes. It provides the quick and efficient method to find low spots on body filler, primer, glazing putties and other repair components.

## MIXING



By Volume: Ready to use  
 Pot Life N/A

## APPLICATION



1. Shake can well before using.
2. Hold can in an upright position and spray 12" from the surface, apply a light even coat over the primed area.
3. Sand (Dry #80 grit, finish #600 grit or Wet: #400 grit, finish #800 grit) until Low Spot Finder Guide Coat is no longer visible.
4. Clean nozzle by inverting can and spraying until mist is clear.

## DRY TIMES



Dry to Sand 1-2 minutes

## PRODUCT SPECIFICATIONS

Color: Black	Shelf Life: 1 year
Size: 20 oz Aero	

## REGULATORY

Category: FCP	9183
MIR	<0.80

## LIMITATIONS & PRECAUTIONS

- Visit [www.tat-co.com](http://www.tat-co.com) to assure use of the most current instructions and TDS on this product.
- See website ([www.tat-co.com](http://www.tat-co.com)) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.
- If mixed with other components, mixture may be hazards of all combined components.
- All Standard Operating Procedures (SOP) can be found on the Transtar website at [www.tat-co.com](http://www.tat-co.com).