

---

# PRODUCT DATA

---

**9203**

## **Paint & Coating Remover**

### **DESCRIPTION:**

Paint & Coating Remover is a unique formula designed to remove a wide variety of coatings including refinish materials from urethane bumpers. Clings to vertical surfaces without sagging. Note: This product will not remove OEM finishes. Attempting to do so can damage the substrate.

### **TECHNICAL DATA:**

SOLVENTS:	Methylene Chloride, Methanol, Isobutane, Propane, n-Butane
V.O.C. CONTENT:	4.88#/gal (586g/l) and 25% V.O.C. by weight
SHELF LIFE:	12 months

### **APPLICATION:**

Shake can well before using. Hold can in an upright position and apply a heavy, even film to surface. PROTECT SURROUNDING AREAS FROM OVERSPRAY. Do not apply in direct sunlight or windy conditions. Allow to stand until coating softens or wrinkles, then (wearing protective rubber gloves) remove coating with squeegee or steel wool. Do not allow stripper to remain on surface for more than ten minutes. Neutralize area with water immediately after removing coating. DO NOT APPLY DIRECTLY TO BARE PLASTIC.

### **SALES POINTS:**

- Convenient aerosol package.
- Fast acting solvents.
- Clings to vertical surfaces.
- Removes wide variety of coatings.

---

*(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).*

### **PACKAGE SIZES:**

#9203 Paint & Coatings Remover, 20 oz. Aerosol, 12/case

*DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*



*This product is not compliant for sale in California or states that have adopted the regulations of the OTC.*