



PRODUCT DATA

9233

Dull Black Reconditioning Paint

DESCRIPTION:

Dull Black Reconditioning Paint is designed to provide the autobody technician duplicate coatings when restoring vehicles to OEM appearance. This fast drying formula will provide easy, durable applications with outstanding results. MIR = 1.38

TECHNICAL DATA:

V.O.C. CONTENT:	5.04 #/gal (604g/l) and less than 52% by weight
MIR VALUE:	1.38
SHELF LIFE:	12 months

APPLICATION:

Shake can well before using. Surface should be clean and dry. For best results, use when temperature is between 70° - 90°F (21° - 32°C). Hold can in an upright position 8 - 10 inches from surface and apply a uniform coating to surface. Several light coats will produce better results than one heavy coat. If clogging develops, turn spray button 1/4 turn or remove and clean button slot. Do not insert objects into can opening. Clear button when finished by inverting can and spraying for two seconds. Discard empty container in EPA approved pick up. Do not incinerate or compact.

SALES POINTS:

- Convenient aerosol package.
- Fast drying.
- Duplicates OEM finishes.
- Durable coating.

(Refer to Material Safety Data Sheet for proper handling of products listed in this bulletin).

PACKAGE SIZES:

9233 Dull Black Reconditioning Paint, 16 oz. Aerosol (473ml), 12/case

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Transtar Autobody Technologies experience and research and is believed to be reliable. As Transtar has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.

