

# Technical Data Sheet

Acry Solvent adhesive cleaner quickly softens and removes adhesives, tar, grease, oil, body sealers, wax, undercoating overspray and silicones. Acry Solvent can also be used as a pre-paint cleaner and conditioner, it leaves no residue on the surface and is safe for use on automotive finishes when used as directed.

## MIXING



By Volume: Ready to use

Pot Life N/A

## APPLICATION



Apply directly to or saturate a clean cloth and rub/buff adhesive or solid area lightly to remove. Repeat if necessary. Note: On freshly painted surfaces use caution not to flood the surface or rub harshly to avoid damage to the finish. On areas where adhesive is thoroughly dry or contaminants are very thick, such as road tar, allow for a few minutes for the Acry Solvent to penetrate. Repeat if necessary.

## PRODUCT SPECIFICATIONS

Color: Clear Liquid	Shelf Life: 1 year
Size: 24 oz Aero (9783), Quart (9784)	

## REGULATORY

Category: Cleaner	9784
VOC Actual	6.59#/gal (790 g/l)
VOC Regulatory	6.59#/gal (790 g/l)
Weight % of Volatiles	100%
Weight % of Water	0
Weight % of Exempt Compounds	0
Volume % of Exempt Compounds	0
Density of Material #/gal	6.59
Category: General Purpose Degreaser	9783
VOC Content	100%

## LIMITATIONS & PRECAUTIONS

- Visit [www.tat-co.com](http://www.tat-co.com) to assure use of the most current instructions and TDS on this product.
- See website ([www.tat-co.com](http://www.tat-co.com)) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.
- Before use, read and follow all TDS, label and SDS precautions.
- If mixed with other components, mixture may be hazards of all combined components.
- All Standard Operating Procedures (SOP) can be found on the Transtar website at [www.tat-co.com](http://www.tat-co.com).