

# SAFETY DATA SHEET.

Issuing date 10-Feb-2020

Revision Date 18-Mar-2020

Version 1.01

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product name**

eCoat DTM Black

**Product number**

4713, 4713-C

**Product code**

**Product Type**

Flammable aerosol

**Synonyms**

None

**Supplier's details**

**Recommended Use**

Auto Body Primer

**Uses advised against**

No information available

**Manufacturer/Supplier:**

Transtar Autobody Technologies  
2040 Heiserman Drive  
Brighton, MI 48116  
800-824-2843

**Emergency telephone number**

**CHEMTREC 24 hr Chemical**

+1-703-741-5970 (INTERNATIONAL)

**Emergency Phone Number**

1-800-424-9300 (NORTH AMERICA)

## 2. HAZARDS IDENTIFICATION

### Classification

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.  
 Flame Extension Test results show the product is extremely flammable for CPSC statements.  
 Flame Ignition Test results show that the product is flammable per GHS classifications.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 2
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Causes skin irritation.  
 Causes serious eye irritation.  
 Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness.  
 May cause damage to organs (Central Nervous System, Eyes, Kidneys, Liver, Respiratory System, and Skin) through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.  
 Flammable aerosol  
 Contains gas under pressure; may explode if heated



**Appearance** Opaque

**Physical state** Aerosol

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves, protective clothing, eye protection, face protection.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Do not breathe dust, fume, gas, mist, vapors, spray.  
 Use only outdoors or in a well-ventilated area.  
 Keep away from heat, sparks, open flames, hot surfaces - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice, attention.

Specific treatment (see first aid on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice, attention

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice, attention.

Take off contaminated clothing and wash it before reuse.

IF INHALED : Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor, physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.

Do NOT induce vomiting.

**Precautionary Statements - Storage**

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents, container to an approved waste disposal plant.

**Hazards not otherwise classified (HNOC)**

None

**Other information**

0% of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %*
DIMETHYLEETHER	115-10-6	30-40
ACETONE	67-64-1	10-20
HYDROTREATED HEAVY NAPHTHENIC	64742-48-9	10-20
TOLUENE	108-88-3	1-10
2-BUTANONE	78-93-3	1-10
CALCIUM CARBONATE	1317-65-3	1-10
CARBON BLACK	1333-86-4	1-10
ETHYL BENZENE	100-41-4	<0.1
BENZENE	71-43-2	<0.1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****First aid measures for different exposure routes****General advice**

Avoid contact with eyes, skin, and clothing.

**Eye contact**

Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. Seek immediate medical attention, advice. If eye irritation persists, consult a doctor.

**Skin contact**

Rinse immediately with plenty of water for 15 minutes and seek medical advice if skin irritation persists.

<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

<b>Main Symptoms</b>	Causes skin and eye irritation. May cause respiratory irritation. May cause dizziness or drowsiness. Harmful and may be fatal if swallowed and enters airways.
----------------------	--

**Indication of immediate medical attention and special treatment needed, if necessary**

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Water fog. Dry chemical. Foam. Carbon dioxide (CO<sub>2</sub>). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable. Keep product and empty container away from heat and sources of ignition.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

In the event of fire and/or explosion do not breathe fumes. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Use with adequate ventilation to keep the exposure levels below the OELS.
-----------------------------	---

**Environmental precautions**

<b>Environmental precautions</b>	Vapors can accumulate in low areas. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.
----------------------------------	---

**Methods and materials for containment and cleaning up**

<b>Methods for Containment</b>	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.
<b>Methods for cleaning up</b>	Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material. Use personal protective equipment. Dam up. Cover liquid spill with sand, earth, or other noncombustible absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Advice on safe handling** Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

**Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep tightly closed in a dry and cool place. Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, oxidizing agents.

**Aerosol Level** 2

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
DIMETHYLETHER 115-10-6	STEL: 500 PPM TWA: 400PPM	TWX: 400 PPM TWA: 1200 mg/m <sup>3</sup>	IDLH: 1900 PPM (10 % LEL)
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
2-BUTANONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m <sup>3</sup> (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm Skin - potential significant contribution to overall exposure	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

	by the cutaneous route	TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	
--	------------------------	--	--

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Exposure controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Tightly fitting safety goggles. Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and chemical properties

<b>Physical state</b>	Aerosol	<b>Odor</b>	Solvent
<b>Appearance</b>	Opaque	<b>Odor Threshold</b>	
<b>Color</b>	Black		
<b>Property</b>	<b>Values</b>	<b>Remarks • Methods</b>	
<b>pH</b>	No information available		
<b>Melting/freezing point</b>	No information available		
<b>Boiling point/boiling range</b>			
<b>Flash Point</b>	-41.1 °C / -42 °F	Based on propellant Flame Extension test results show this product to be extremely flammable for CPSC labelling statements. Flame Ignition test results show the product to be flammable for GHS flammable classifications in Section 2.	
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limits in Air</b>			
upper flammability limit			
lower flammability limit			
<b>Vapor pressure</b>			
<b>Vapor density</b>			
<b>Specific Gravity</b>	0.820		

<b>Water solubility</b>	Practically insoluble
<b>Partition coefficient: n-octanol/water</b>	
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	
<b>Viscosity</b>	No information available
<b>Explosive properties</b>	

**Other information**

<b>VOC Content(%)</b>	65.74
<b>MIR Value</b>	0.91
<b>MIR Coating Category</b>	ABP (Auto body primers) MIR <0.95 CALIFORNIA ABP < 1.55 EPA

## 10. STABILITY AND REACTIVITY

**Reactivity**

Stable under recommended storage conditions

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Heat, flames and sparks.

**Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

**Hazardous Decomposition Products**

Carbon oxides , Hydrocarbons, Fumes.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory system.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Causes skin irritation.
<b>Ingestion</b>	Harmful and may be fatal if swallowed and enters airways and lungs.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER 115-10-6	-	-	= 164000 ppm ( Rat ) 4 h
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	> 6000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	> 8500 mg/m <sup>3</sup> ( Rat ) 4 h
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
2-BUTANONE	= 2483 mg/kg ( Rat ) = 2737 mg/kg	= 5000 mg/kg ( Rabbit ) = 6480	= 11700 ppm ( Rat ) 4 h

78-93-3	( Rat )	mg/kg ( Rabbit )	
CARBON BLACK 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
BENZENE 71-43-2	= 1800 mg/kg ( Rat ) = 810 mg/kg ( Rat )	> 8200 mg/kg ( Rabbit )	= 44.66 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Causes eye and skin irritation. May cause respiratory irritation. May cause drowsiness and dizziness. Harmful if swallowed and enters airways.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Causes skin irritation.  
**Eye damage/irritation** Irritating to eyes.  
**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.  
 Ethyl Benzene and Benzene are in the product at <0.1 % reportable levels.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	X
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
BENZENE 71-43-2	A1	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

**Reproductive toxicity** Product is or contains a chemical which is a known or suspected reproductive hazard.  
**Specific target organ systemic toxicity (single exposure)** May cause respiratory irritation. May cause drowsiness or dizziness.  
**Specific target organ systemic toxicity (repeated exposure)** May cause damage to Target Organs listed below through prolonged or repeated exposure.  
**Chronic toxicity** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.  
**Target Organ Effects** Eyes, Skin, Respiratory System, Central Nervous System, Kidney, and Liver.  
**Aspiration hazard** May be fatal if swallowed and enters airways.

### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 16728 mg/kg

ATEmix (dermal) 22332 mg/kg

ATEmix (inhalation-gas) 63433 mg/l

ATEmix (inhalation-vapor) 167.3 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates



DIMETHYLETHER 115-10-6	-	4.1 g/L LC50 <i>Poecilia reticulata</i> 96h semi-static	-	-
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 <i>Oncorhynchus mykiss</i> 96h 6210 - 8120 mg/L LC50 <i>Pimephales promelas</i> 96h static 8300 mg/L LC50 <i>Lepomis macrochirus</i> 96h	-	10294 - 17704 mg/L EC50 <i>Daphnia magna</i> 48h Static 12600 - 12700 mg/L EC50 <i>Daphnia magna</i> 48h
HYDROTREATED HEAVY NAPHTHENIC 64742-48-9	-	2200 mg/L LC50 <i>Pimephales promelas</i> 96h	-	2.6 mg/L LC50 <i>Chaetogammarus marinus</i> 96h
TOLUENE 108-88-3	12.5 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 72h static 433 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 96h	11.0 - 15.0 mg/L LC50 <i>Lepomis macrochirus</i> 96h static 14.1 - 17.16 mg/L LC50 <i>Oncorhynchus mykiss</i> 96h static 15.22 - 19.05 mg/L LC50 <i>Pimephales</i> <i>promelas</i> 96h flow-through 5.89 - 7.81 mg/L LC50 <i>Oncorhynchus mykiss</i> 96h flow-through 50.87 - 70.34 mg/L LC50 <i>Poecilia</i> <i>reticulata</i> 96h static 12.6 mg/L LC50 <i>Pimephales</i> <i>promelas</i> 96h static 28.2 mg/L LC50 <i>Poecilia</i> <i>reticulata</i> 96h semi-static 5.8 mg/L LC50 <i>Oncorhynchus</i> <i>mykiss</i> 96h semi-static 54 mg/L LC50 <i>Oryzias latipes</i> 96h static	-	5.46 - 9.83 mg/L EC50 <i>Daphnia magna</i> 48h Static 11.5 mg/L EC50 <i>Daphnia</i> <i>magna</i> 48h
2-BUTANONE 78-93-3	-	3130 - 3320 mg/L LC50 <i>Pimephales promelas</i> 96h flow-through	-	4025 - 6440 mg/L EC50 <i>Daphnia magna</i> 48h Static 5091 mg/L EC50 <i>Daphnia</i> <i>magna</i> 48h 520 mg/L EC50 <i>Daphnia magna</i> 48h
CARBON BLACK 1333-86-4	-	-	-	5600 mg/L EC50 <i>Daphnia</i> <i>magna</i> 24h
ETHYL BENZENE 100-41-4	1.7 - 7.6 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 96h static 2.6 - 11.3 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 72h static 4.6 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 72h 438 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 96h	11.0 - 18.0 mg/L LC50 <i>Oncorhynchus mykiss</i> 96h static 7.55 - 11 mg/L LC50 <i>Pimephales promelas</i> 96h flow-through 9.1 - 15.6 mg/L LC50 <i>Pimephales promelas</i> 96h static 32 mg/L LC50 <i>Lepomis macrochirus</i> 96h static 4.2 mg/L LC50 <i>Oncorhynchus mykiss</i> 96h semi-static 9.6 mg/L LC50 <i>Poecilia reticulata</i> 96h static	-	1.8 - 2.4 mg/L EC50 <i>Daphnia magna</i> 48h
BENZENE 71-43-2	29 mg/L EC50 <i>Pseudokirchneriella</i> subcapitata 72h	10.7 - 14.7 mg/L LC50 <i>Pimephales promelas</i> 96h flow-through 22330 - 41160 µg/L LC50 <i>Pimephales</i> <i>promelas</i> 96h static 70000 - 142000 µg/L LC50 <i>Lepomis</i> <i>macrochirus</i> 96h static 22.49 mg/L LC50 <i>Lepomis</i> <i>macrochirus</i> 96h static 28.6 mg/L LC50 <i>Poecilia</i> <i>reticulata</i> 96h static 5.3 mg/L LC50 <i>Oncorhynchus mykiss</i> 96h flow-through	-	8.76 - 15.6 mg/L EC50 <i>Daphnia magna</i> 48h Static 10 mg/L EC50 <i>Daphnia</i> <i>magna</i> 48h

**Persistence and degradability****Bioaccumulation**

Chemical Name	log Pow
DIMETHYLETHER 115-10-6	-0.18
ACETONE 67-64-1	-0.24
TOLUENE 108-88-3	2.7
2-BUTANONE 78-93-3	0.3
ETHYL BENZENE 100-41-4	3.2
BENZENE 71-43-2	2.1

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

**IMDG** UN1950, AEROSOLS, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
DIMETHYLETHER	X	X	X	X	X	X	X	X
ACETONE	X	X	X	X	X	X	X	X
HYDROTREATED HEAVY NAPHTHENIC	X	X	X	Not listed	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
2-BUTANONE	X	X	X	X	X	X	X	X
CALCIUM CARBONATE	X	X	X	X	X	X	X	X
CARBON BLACK	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
BENZENE	X	X	X	X	X	X	X	X

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**CHINA** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	<0.1	0.1
BENZENE - 71-43-2	71-43-2	<0.1	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

**Clean Water Act**

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE 71-43-2	10 lb	X	X	X

**CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
2-BUTANONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE 71-43-2	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

**U.S. State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental/ 1-10%
CARBON BLACK - 1333-86-4	Cancer/ not airborne or particle size <10 micrometers, tied up in a polymer.(does not apply for this product)/ 1-10%
ETHYL BENZENE - 100-41-4	Cancer/ <0.1%
BENZENE - 71-43-2	Cancer Developmental (Male) /<0.1%

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
DIMETHYLETHER 115-10-6	X	X	X
ACETONE 67-64-1	X	X	X
TOLUENE 108-88-3	X	X	X
2-BUTANONE 78-93-3	X	X	X
CALCIUM CARBONATE 1317-65-3	X	X	X
CARBON BLACK 1333-86-4	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE 71-43-2	X	X	X

**EPA Pesticide Registration Number** Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

<b>NFPA</b>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<b>HMIS</b>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B
<i>Chronic Hazard Star Legend</i>		<i>Repeated or prolonged exposure may cause central nervous system damage</i>		<i>Chronic Health Star</i>

**Prepared By** Transtar Autobody Technologies

---

Issuing date 10-Feb-2020

Revision Date 18-Mar-2020

**Revision Note**

(M)SDS sections updated 3 15

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**