

# SAFETY DATA SHEET

## Section 1 - Product and Company Identification

Product Name: Super Sand

Product Code: 6051, 6055

Manufacturer/Supplier:

TRANSTAR AUTOBODY TECHNOLOGIES

2040 Heiserman Dr.

Brighton, MI, 48114, USA

**24 Hour Emergency Phone(s):**

USA 800-424-9300 (CHEMTREC)

International 001-703-527-3887 (CHEMTREC Int'l)

Business Phone: 810-360-1600

SDS Prepared By: Transtar Autobody Technologies

Product Use: Primer. For Professional and Industrial Use Only

Not recommended for: Not for Sale to General Public

## Section 2 - Hazards Identification

### Classification of the substance or mixture

#### GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Mutagen	2	Suspected/Possible: May include heritable mutations in human germ cells, Positive evidence from tests in mammals and somatic cell tests, In vivo somatic genotoxicity supported by in vitro mutagenicity
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Reproductive toxin	1A	Known or presumed to cause effects on human reproduction or on development
Organ toxin single exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance) - Human evidence in exceptional cases
Organ toxin repeated exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance)- Human evidence in exceptional cases
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm <sup>2</sup> /s at 40° C.
Aquatic toxicity	A2	Acute toxicity > 1.00 but <= 10.0 mg/l

#### GHS Hazards

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H341	Suspected of causing genetic defects
H350	May cause cancer

#### GHS Precautions

P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood

H360 May damage fertility or the unborn child  
 H371 May cause damage to organs  
 H373 May cause damage to organs through prolonged or repeated exposure  
 H401 Toxic to aquatic life

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking  
 P233 Keep container tightly closed  
 P240 Ground and bond container and receiving equipment  
 P241 Use explosion-proof electrical, ventilating, lighting and motorized equipment  
 P242 Use only non-sparking tools  
 P243 Take precautionary measures against static discharge  
 P260 Do not breathe dust, mist, vapors or spray  
 P264 Wash contacted skin thoroughly after handling  
 P270 Do not eat, drink or smoke when using this product  
 P273 Avoid release to the environment  
 P280 Wear protective gloves, protective clothing, eye protection, face protection and respiratory protection.  
 P321 Specific treatment (see first aid instructions on SDS)  
 P331 Do NOT induce vomiting  
 P362 Take off contaminated clothing and wash before reuse  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 P303+P361+P353 IF ON SKIN (or hair): Immediately take off all contaminated clothing. Wash skin with soap and water.  
 P308+P313 IF exposed or concerned: Get medical advice  
 P332+P313 If skin irritation occurs: Get medical advice  
 P370+P378 In case of fire: Use dry chemical, CO2, foam or water fog to extinguish  
 P405 Store locked up  
 P403+P235 Store in a well ventilated place. Keep cool  
 P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

**Danger**



**Hazards not otherwise classified (HNOC) or not covered by GHS:**

None known

**Section 3 - Composition**

<b>Chemical Name / CAS No.</b>	<b>OSHA Exposure Limits</b>	<b>ACGIH Exposure Limits</b>	<b>Other Exposure Limits</b>
Toluene 108-88-3 20 to 30%	200 ppm TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 375 mg/m <sup>3</sup> TWA 150 ppm STEL; 560 mg/m <sup>3</sup> STEL
Talc 14807-96-6 10 to 20%	PEL-TWA is 20 mppcf (million particles per cubic foot of air).	2 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	NIOSH: 2 mg/m <sup>3</sup> TWA (containing no Asbestos and <1% Quartz, respirable dust)
Barium Sulfate 7727-43-7 5 to 10%	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	5 mg/m <sup>3</sup> TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)
Xylene 1330-20-7 5 to 10%	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	150 ppm STEL 100 ppm TWA	
Titanium Dioxide (Dust) 13463-67-7 5 to 10%	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
Methyl Ethyl Ketone 78-93-3 5 to 10%	200 ppm TWA; 590 mg/m <sup>3</sup> TWA	300 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 590 mg/m <sup>3</sup> TWA 300 ppm STEL; 885 mg/m <sup>3</sup> STEL
Anhydrous Aluminum Silicate 66402-68-4 1 to 5%	15mg/m <sup>3</sup> (Total dust) TWA 8 hours 5mg/m <sup>3</sup> (Respirable dust) TWA 8 hours	2mg/m <sup>3</sup> (Respirable dust) TWA 8 hours	10mg/m <sup>3</sup> (Total dust) TWA 10 hours
Ethylbenzene 100-41-4 1 to 5%	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m <sup>3</sup> TWA 125 ppm STEL; 545 mg/m <sup>3</sup> STEL
Propylene glycol monomethyl ether acetate 108-65-6 1 to 5%	TWA 200 ppm	TWA 50ppm	
Butyl Benzyl Phthalate 85-68-7 1 to 5%	Not Available	Not Available	
Silica, Amorphous 7631-86-9 0.1 to 1.0%	OSHA has set a TWA of 20 mppcf or (80 mg/m <sup>3</sup> /% SiO <sub>2</sub> ).	The ACGIH has set a TWA of 10 mg/m <sup>3</sup> as inhalable particulate and 3 mg/m <sup>3</sup> as respirable particulates.	NIOSH: 6 mg/m <sup>3</sup> TWA
Silica, Crystalline 14808-60-7 0.1 to 1.0%	TWA TOTAL DUST = (30mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2), TWA RESPIRABLE FRACTION = (10mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2)	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	NIOSH: 0.05 mg/m <sup>3</sup> TWA (respirable dust)
Carbon Black 1333-86-4 0.1 to 1.0%	3.5 mg/m <sup>3</sup> TWA	3 mg/m <sup>3</sup> TWA (inhalable fraction)	NIOSH: 3.5 mg/m <sup>3</sup> TWA; 0.1 mg/m <sup>3</sup> TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

---

---

## Section 4 - First Aid Measures

**INHALATION:** If Inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing difficulty persists, seek medical attention.

**EYE CONTACT:** Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for a minimum of 15 minutes while holding eye lids open. If eye irritation persists: seek medical attention.

**SKIN CONTACT:** Take off all contaminated clothing immediately. Wash exposed area thoroughly with soap and water. Seek medical attention if irritation persists. Do NOT use solvents or thinners to wash off.

**INGESTION:** If swallowed, seek medical attention immediately and have product container or label at hand. DO NOT INDUCE VOMITING unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed:**

Dizziness, breathing difficulty, headaches, & loss of coordination.

**Indication of any immediate medical attention and special treatment needed.**

Seek professional medical attention for all over-exposures and/or persistent problems.

## Section 5 - Fire Fighting Measures

LEL: 1.0 %

UEL: 11.4 %

**Extinguishing Media:** Dry Chemical, Foam, CO2 or water fog.

**Unsuitable Extinguishing Media:** High volume water jets

**Unusual Fire and Explosion Hazards:** Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat or burst when contaminated with water (CO2 gas evolved). Hazards apply to empty containers. Combustion generates toxic fumes.

**Hazardous Combustion Products:** oxides of carbon, oxides of nitrogen, formaldehyde, toxic fume

**Special Firefighting Procedures:** Highly toxic fumes may be generated by thermal decomposition. Water runoff from firefighting can cause environmental damage. Dike and collect water used to fight fire.

**Fire Equipment:** Full fire fighter equipment including SCBA should be worn to avoid skin contact and inhalation of concentrated vapors. Minimize skin exposure.

## Section 6 - Accidental Release Measures

**Personal precautions, protective equipment and emergency procedures:**

Use personal protective equipment. Avoid breathing vapors and mist. Ensure adequate ventilation. Eliminate all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulation to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

**Environmental precautions:**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

**Methods and materials for containment and cleaning up:**

Dike spill area and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite,

diatomaceous earth. Sweep up and dispose of in appropriate containers in accordance to Federal, State and/or Local regulations. Clean preferably with a detergent; avoid use of solvents.

## Section 7 - Handling and Storage

**Safe Handling Measures:** Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Ground and bond container and receiving equipment. Use non-sparking tools and explosion proof equipment when handling this material. Keep away from sources of ignition - No Smoking. Use in cool, well-ventilated areas. Keep containers closed when not in use. Take measures to prevent the build up of electrostatic charge. Follow all SDS and label precautions even after container is emptied because they may retain product residues. For precautions see section 2.

**Storage Requirements:** Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces-No Smoking. Store in a cool, dry and well-ventilated place. Do not reuse container when empty.

## Section 8 - Exposure Control and PPE

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Toluene 108-88-3	200 ppm TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 375 mg/m <sup>3</sup> TWA 150 ppm STEL; 560 mg/m <sup>3</sup> STEL
Talc 14807-96-6	PEL-TWA is 20 mppcf (million particles per cubic foot of air).	2 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	NIOSH: 2 mg/m <sup>3</sup> TWA (containing no Asbestos and <1% Quartz, respirable dust)
Barium Sulfate 7727-43-7	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	5 mg/m <sup>3</sup> TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)
Xylene 1330-20-7	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	150 ppm STEL 100 ppm TWA	
Titanium Dioxide (Dust) 13463-67-7	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
Methyl Ethyl Ketone 78-93-3	200 ppm TWA; 590 mg/m <sup>3</sup> TWA	300 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 590 mg/m <sup>3</sup> TWA 300 ppm STEL; 885 mg/m <sup>3</sup> STEL
Anhydrous Aluminum Silicate 66402-68-4	15mg/m <sup>3</sup> (Total dust) TWA 8 hours 5mg/m <sup>3</sup> (Respirable dust) TWA 8 hours	2mg/m <sup>3</sup> (Respirable dust) TWA 8 hours	10mg/m <sup>3</sup> (Total dust) TWA 10 hours
Ethylbenzene 100-41-4	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m <sup>3</sup> TWA 125 ppm STEL; 545 mg/m <sup>3</sup> STEL
Propylene glycol monomethyl ether acetate 108-65-6	TWA 200 ppm	TWA 50ppm	
Butyl Benzyl Phthalate 85-68-7	Not Available	Not Available	

Silica, Amorphous 7631-86-9	OSHA has set a TWA of 20 mppcf or (80 mg/m3/% SiO2).	The ACGIH has set a TWA of 10 mg/m3 as inhalable particulate and 3 mg/m3 as respirable particulates.	NIOSH: 6 mg/m3 TWA
Silica, Crystalline 14808-60-7	TWA TOTAL DUST = (30mg/m3)/(%SiO2+2), TWA RESPIRABLE FRACTION = (10mg/m3)/(%SiO2+2)	0.025 mg/m3 TWA (respirable fraction)	NIOSH: 0.05 mg/m3 TWA (respirable dust)
Carbon Black 1333-86-4	3.5 mg/m3 TWA	3 mg/m3 TWA (inhalable fraction)	NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

**Engineering Controls:** Ground and bond container and reciving equipment. Use explosion proof electrical, ventilation, lighting and motorized equipment. Use non-sparking tools. Ensure adequate ventilation.

**Ventilation:** General mechanical ventilation or local exhaust should be utilized to keep vapor concentrations below exposure limits (PEL & TLV). Ventilation equipment must be explosion proof.

**Safe Work Practices:** Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands thoroughly after using and before eating, drinking or smoking . Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used. Spraying of material can cause and oxygen deficient environment. Use proper ventilation to remove vapors, mist and fumes combined with NIOSH approved respirator.

**Respiratory Protection:** When working with this material use a MSHA/NIOSH approved cartridge respirator or suitable respiratory protection to keep airborne mists and vapor concentrations below the PEL & TLV limits . When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

**Eye/Face Protection:** Use safety glasses with chemical splash goggles or faceshield.

**Skin Protection:** Use chemical resistant gloves.

**Body Protection:** Impervious clothing, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Contaminated Gear:** Take off contaminated clothing immediately and wash before reuse .

## Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<p><b>Appearance</b> Gray</p> <p><b>Odor</b> Organic Solvent</p> <p><b>pH:</b> No data available</p> <p><b>Freezing point:</b> No data available</p> <p><b>Flash point:</b> 16 F,-9 C</p> <p><b>Flammability:</b> No data available</p> <p><b>Vapor Pressure:</b> 25.5 mmHg</p> <p><b>Density (Lb / Gal)</b> 10.85</p>	<p><b>Physical State</b> Liquid</p> <p><b>Odor threshold:</b> No data available</p> <p><b>Melting point:</b> No data available</p> <p><b>Boiling range:</b> 80°C</p> <p><b>Evaporation rate:</b> No data available</p> <p><b>Explosive Limits:</b> 1% - 11%</p> <p><b>Vapor Density:</b> 3.8</p> <p><b>Solubility:</b> No data available</p>
--	--

<b>Partition coefficient (n- No data available octanol/water):</b> <b>Decomposition temperature:</b> No data available <b>Regulatory Coating VOC g/L</b> 556  <b>Actual Coating VOC g/L</b> 556 <b>Weight Percent Volatile</b> 42.81 % <b>Weight VOC</b> 42.78 % <b>Wt Exempt VOC</b> 0.00	<b>Autoignition temperature:</b> 315°C  <b>Viscosity:</b> No data available <b>Regulatory Coating VOC</b> 4.64 <b>lb/gal</b> <b>Actual Coating VOC lb/Gal</b> 4.64 <b>Specific Gravity (SG)</b> 1.300 % <b>Weight Water</b> 0.0 % <b>Vol Exempt VOC</b> 0.00
---	--

## Section 10 - Stability and Reactivity

**Reactivity:** No data available

**Stability:** Stable under recommended storage conditions.

**Possibility of hazardous reactions:** Vapors may form explosive mixture with air. Hazardous polymerization will not occur.

**Conditions to avoid:** Heat, flame and sparks. Extreme temperature and direct sunlight.

**Incompatible with:**

- Strong oxidizers
- Strong bases
- Strong oxidizing agents
- Acids

**Hazardous products produced under decomposition:**

Carbon Monoxide, Carbon Dioxide .

## Section 11 - Toxicological Information

**Mixture Toxicity**

Inhalation Toxicity: 34mg/L

**Component Toxicity**

- |           |  |
|-----------|--|
| 108-88-3  | Toluene<br>Oral: 2,600 mg/kg (Rat) Inhalation: 13 mg/L (Rat)                             |
| 1330-20-7 | Xylene<br>Oral: 3,500 mg/kg (Rat) Dermal: 4,350 mg/kg (Rabbit) Inhalation: 29 mg/L (Rat) |
| 78-93-3   | Methyl Ethyl Ketone<br>Oral: 2,483 mg/kg (Rat) Dermal: 5,000 mg/kg (Rabbit)              |
| 100-41-4  | Ethylbenzene<br>Oral: 3,500 mg/kg (Rat) Inhalation: 17 mg/L (Rat)                        |
| 108-65-6  | Propylene glycol monomethyl ether acetate<br>Dermal: 5 g/kg (Rabbit)                     |
| 7631-86-9 | Silica, Amorphous<br>Dermal: 2,000 mg/kg (Rabbit) Inhalation: 2 mg/L (Rat)               |

This mixture has not been tested for toxicological effects .

**Acute Effects:**

INHALATION - Dizziness, breathing difficulty, headaches, & loss of coordination .  
EYE CONTACT - Moderate irritation, tearing, redness, and blurred vision .

SKIN CONTACT - Moderate irritant. Can dry and defat skin causing cracks, irritation, and dermatitis.  
 INGESTION - Can cause gastrointestinal irritation, vomiting, nausea, & diarrhea.

**Chronic Effects:**

May affect liver, kidney and central nervous system with repeated exposure . Prolonged or repeated exposure may cause lung injury.

**Routes of Entry**

<b>Inhalation</b>	<b>Skin Contact</b>	<b>Eye Contact</b>	<b>Ingestion</b>
<b>Target Organs</b>			
<b>Blood</b>	<b>Eyes</b>	<b>Kidneys</b>	<b>Liver</b>
<b>Cardiovascular System</b>	<b>Respiratory System</b>	<b>Lungs</b>	<b>Central Nervous System</b>
			<b>Skin</b>

**Effects of Overexposure**

Short Term Exposure

Irritates the eyes and the respiratory tract. May affect the central nervous system. Inhalation may cause irritation to respiratory tract. Skin contact may cause irritation. Eye contact may cause irritation. Ethyl benzene irritates the eyes, skin, and respiratory tract. Exposure to high concentrations can cause dizziness, lightheadedness and unconsciousness. Very high exposures (above the OEL) can cause difficult breathing, narcosis, coma, and even death. Swallowing the liquid may cause aspiration into the lungs, resulting in chemical pneumonitis. May affect the central nervous system. Concentration of 200 ppm can cause irritation. Inhalation: Exposure to vapor can be irritation to the nose and throat. Inhalation of vapor at concentrations above 200 ppm or 3 - 5 minutes can lead to xylene intoxication. Symptoms include headache, dizziness, nausea and vomiting. If exposure should continue, central nervous system depression characterized by shallow breathing and weak pulse can occur. Levels of 230 ppm for 15 minutes may cause lightheadedness without loss of equilibrium. Reversible liver and kidney damage in man has followed exposure to sudden high concentrations of vapor. Such high levels may also give rise to lung congestion. Exposure to extremely high concentrations (10,000 ppm or more) of xylene vapors can lead to a strong narcotic effect with symptoms of slurred speech, stupor fatigue, confusion, unconsciousness, coma, and possible death. Irritates the eyes, the skin and the respiratory tract. Skin contact may cause a burning sensation. High levels of this chemical may cause dizziness and lightheadedness. The oral LD50 rat is 2,330 mg/kg (slightly toxic). Irritates the eyes and respiratory tract. Causes central nervous system depression. High levels of exposure may cause fatigue, weakness, confusion, euphoria, dizziness, headache; dilated pupils, lacrimation (discharge of tears); nervousness, muscle fatigue, insomnia; paresthesia; cardiac dysrhythmia, unconsciousness and death may occur. Inhalation: 100 ppm exposure can cause dizziness, drowsiness and hallucinations. 100 - 200 ppm can cause depression, 200 - 500 ppm can cause headaches, nausea, loss of appetite, loss of energy, loss of coordination and coma. In addition to the above, death has resulted from exposure to 10,000 ppm for an unknown time. Skin: Can cause dryness and irritation. Absorption may cause or increase the severity of symptoms listed above. Eyes: Can cause irritation at 300 ppm. Ingestion: Can cause a burning sensation in the mouth and stomach, upper abdominal pain, cough, hoarseness, headache, nausea, loss of appetite, loss of energy, loss of coordination and coma . Irritates the eyes. Inhalation can cause cough, dyspnea (breathing difficulty), wheezing . Inhalation can cause irritation of the eyes and respiratory tract, causing cough and phlegm. Irritates the skin. Amorphous fused silica can affect you when breathed in . Exposure can cause a very serious lung disease called silicosis, with cough and shortness of breath. Very high exposures can cause this problem to develop in a few weeks, or with lower exposures it may occur over many years. Silicosis can cause death. If silicosis develops, chances of getting tuberculosis are increased. The disease may progress, with or without continued exposure. If it does, this can be crippling or even fatal.

Long Term Exposure

Repeated exposure can cause drying and cracking of the skin. Has been implicated in certain nervous system and brain disorders characterized by weakness, fatigue, sleep disturbances, reduced coordination, heaviness in chest and numbness of hand and feet. These symptoms may develop after 1 year of exposure to vapor concentrations of 50 - 200 ppm. Improvement is gradual and may take years after exposure is discontinued. Animal tests show that this chemical is a teratogen in animals and possibly causes toxic effects upon human reproduction. Exposure to levels well above 3.5 mg/m<sup>3</sup> for several months may result in damage to the skin and nails, temporary or permanent damage to the lungs and breathing passages, and adversely affect the heart. Carbon Black containing PAH greater than 0.1% should be considered a suspect carcinogen. Lungs may be affected by repeated or prolonged exposure at very high concentrations: Some Carbon blacks may contain compounds which are carcinogenic and as organic extracts of these have been classified as possibly carcinogenic to humans, special care should be taken to avoid exposure to such extracts. Lung effects remain controversial and may be due to contaminants. It is probable that minor effects reported are non-specific effects associated with exposure to nuisance dusts in general. Polyaromatic hydrocarbons (PAH) are reportedly present in some carbon blacks. Depending on the process of manufacture, there are variations in their chemical compositions. Repeated or prolonged exposure to the skin may cause drying, scaling and blistering. May cause kidney disease, liver disease, chronic respiratory disease, skin disease, as follows: EB is not nephrotoxic. Concern is expressed because the kidney is the primary route of excretion of EB and its metabolites. EB is not hepatotoxic. Since EB is metabolized by the liver, concern is expressed for these tissues. Exacerbation of pulmonary pathology might occur following exposure to EB. Individuals with impaired pulmonary function might be at risk. EB is a defating agent and may cause dermatitis following prolonged exposure. Individuals with preexisting skin problems may be more sensitive to EB. There is limited evidence that EB may damage the developing fetus, and may cause mutations. Inhalation of xylene vapor and skin contact with liquid are the two most probable routes of long term exposure. Symptoms of inhalation are dizziness, headache and nausea. Long term exposure has been associated with liver and kidney damage, intestinal tract disturbances and central nervous system depression. Prolonged contact with skin can lead to irritation, dryness and cracking. Repeated exposure can cause poor memory, difficulty in concentration, and other brain effects. It can also cause damage to the eye surface. Listed by NTP as an animal carcinogen. No data for humans. May affect liver and kidney function. Repeated exposure may damage the nervous system, causing weakness, "pins and needles," and poor coordination in arms and legs. Repeated or prolonged contact with skin may cause dermatitis; drying, cracking, itching, and skin rash. May cause liver, kidney, and brain damage; decreased learning ability, psychological disorders. Levels below 200 ppm may produce headache, tiredness and nausea. From 200 - 750 ppm symptoms may include insomnia, irritability, dizziness, some loss of memory, cause heart palpitations and loss of coordination. Blood effects and anemia have been reported but are probably due to contamination by benzene. Can cause decreased pulmonary function, progressive respiratory symptoms; fibrosis (silicosis). A potential occupational carcinogen. Silicosis is a very serious lung disease and can cause with cough and shortness of breath. Silicosis can develop in a few weeks at very high exposures, or it may occur over many years with lower exposures. Silicosis can cause death. If silicosis develops, risk of developing tuberculosis is increased. The disease may progress with or without continued exposure. If it does, this can be crippling or even fatal. Very fine silica, or "silica flour" is even more hazardous. High exposures may cause lung irritation; bronchitis may develop. Continued exposure may result in emphysema, lung scarring, lung fibrosis, and tumors. A potential occupational carcinogen.

The following chemicals comprise of at least 0.1% of this mixture and are listed and/or classified as carcinogens or potential carcinogens by the NTP, IARC, OSHA (mandatory listing) or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

1333-86-4	Carbon Black	0.1 to 1.0%	Carbon Black: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
100-41-4	Ethylbenzene	1 to 5%	Ethylbenzene: IARC: Possible human carcinogen OSHA: listed
14808-60-7	Silica, Crystalline	0.1 to 1.0%	Silica, Crystalline: NIOSH: potential occupational carcinogen IARC: Human carcinogen OSHA: listed
13463-67-7	Titanium Dioxide (Dust)	5 to 10%	Titanium Dioxide (Dust): NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
7631-86-9	Silica, Amorphous	0.1 to 1.0%	Silica, Amorphous:

## Section 12 - Ecological Information

This material has not been tested for ecological effects.

**Persistence and degradability:** No data available

**Bioaccumulative potential:** No data available

**Mobility in soil:** No data available

**Other adverse effects:** Contains photochemically reactive solvent.

### Component Ecotoxicity

Toluene

96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-through] (1 day old);  
96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-static];  
96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static];  
96 Hr LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static]  
48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48 Hr EC50 Daphnia magna: 11.5 mg/L  
96 Hr EC50 Pseudokirchneriella subcapitata: >433 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static]

Talc

96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]

Xylene

96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: >780 mg/L; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static]  
48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L

Methyl Ethyl Ketone	96 Hr LC50 Pimephales promelas: 3130 - 3320 mg/L [flow-through] 48 Hr EC50 Daphnia magna: >520 mg/L; 48 Hr EC50 Daphnia magna: 5091 mg/L; 48 Hr EC50 Daphnia magna: 4025 - 6440 mg/L [Static]
Ethylbenzene	96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]
Propylene glycol monomethyl ether acetate	96 Hr LC50 Pimephales promelas: 161 mg/L [static] 48 Hr EC50 Daphnia magna: >500 mg/L
Butyl Benzyl Phthalate	96 Hr LC50 Oncorhynchus mykiss: 1.0 - 10.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 0.82 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 1.39 - 3.88 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: >0.78 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 1.0 - 10.0 mg/L [static] 48 Hr EC50 Daphnia magna: 0.9 - 1.1 mg/L [Static]; 48 Hr EC50 Daphnia magna: >0.76 mg/L [Flow through]; 48 Hr EC50 Daphnia magna: 1.28 mg/L [semi-static]; 48 Hr EC50 Daphnia magna: 0.97 mg/L 96 Hr EC50 Pseudokirchneriella subcapitata: 0.02 - 0.25 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 0.2 - 28.2 mg/L
Silica, Amorphous	96 Hr LC50 Brachydanio rerio: 5000 mg/L [static] 48 Hr EC50 Ceriodaphnia dubia: 7600 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 440 mg/L

## Section 13 - Disposal Considerations

Product should be disposed of in accordance with all Federal, State and local regulations. Contact a licensed professional waste disposal service to dispose of this material. Subject to hazardous waste generation, treatment, storage and disposal rules under RCRA, 40CFR261.

## Section 14 - Transportation Information

The following transportation information is provided based on Transtar Autobody Technologies interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport .

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
IATA	Paint	UN1263	II	3
IMDG	Paint	UN1263	II	3
USDOT	Paint	UN1263	II	3

## Section 15 - Regulatory Information

The information listed in this section is not all inclusive of all regulations for this product or the chemical components of this product.

### California Hazardous Substance List:

- None

### HAPS: This formulation contains the following HAPS:

100-41-4 Ethylbenzene 1 to 5 %  
1330-20-7 Xylene 5 to 10 %

108-88-3 Toluene 20 to 30 %

**NJ RTK:** The following chemicals are listed under New Jersey RTK

1333-86-4 Carbon Black 0.1 to 1.0 %  
14808-60-7 Silica, Crystalline 0.1 to 1.0 %  
7631-86-9 Silica, Amorphous 0.1 to 1.0 %  
85-68-7 Butyl Benzyl Phthalate 1 to 5 %  
100-41-4 Ethylbenzene 1 to 5 %  
78-93-3 Methyl Ethyl Ketone 5 to 10 %  
13463-67-7 Titanium Dioxide (Dust) 5 to 10 %  
1330-20-7 Xylene 5 to 10 %  
7727-43-7 Barium Sulfate 5 to 10 %  
14807-96-6 Talc 10 to 20 %  
108-88-3 Toluene 20 to 30 %

**California Proposition 65**

WARNING: This product contains the following chemical(s) known to the State of California to cause birth defects or other reproductive harm.

85-68-7 Butyl Benzyl Phthalate 1 to 5 %  
108-88-3 Toluene 20 to 30 %

**California Proposition 65**

WARNING: This product contains the following chemical(s) known to the State of California to cause cancer .

1333-86-4 Carbon Black 0.1 to 1.0 %  
14808-60-7 Silica, Crystalline 0.1 to 1.0 %  
100-41-4 Ethylbenzene 1 to 5 %  
13463-67-7 Titanium Dioxide (Dust) 5 to 10 %

**PA RTK:** The following chemicals are listed under Pennsylvania RTK:

1333-86-4 Carbon Black 0.1 to 1.0 %  
14808-60-7 Silica, Crystalline 0.1 to 1.0 %  
7631-86-9 Silica, Amorphous 0.1 to 1.0 %  
85-68-7 Butyl Benzyl Phthalate 1 to 5 %  
100-41-4 Ethylbenzene 1 to 5 %  
78-93-3 Methyl Ethyl Ketone 5 to 10 %  
13463-67-7 Titanium Dioxide (Dust) 5 to 10 %  
1330-20-7 Xylene 5 to 10 %  
7727-43-7 Barium Sulfate 5 to 10 %  
14807-96-6 Talc 10 to 20 %  
108-88-3 Toluene 20 to 30 %

**EU REACH SIN:** The chemicals listed below are on the EU REACH SIN list

85-68-7 1 to 5 %

**SARA 312:** This Product contains the following chemicals subject to the reporting requirements of SARA 312:

100-41-4 Ethylbenzene 1 to 5 %  
78-93-3 Methyl Ethyl Ketone 5 to 10 %  
108-88-3 Toluene 20 to 30 %

**SARA 313:** This Product contains the following chemicals subject to the reporting requirements of SARA 313:

100-41-4 Ethylbenzene 1 to 5 %  
78-93-3 Methyl Ethyl Ketone 5 to 10 %  
108-88-3 Toluene 20 to 30 %

**WHMIS:**

1333-86-4 Carbon Black 0.1 to 1.0 %  
14808-60-7 Silica, Crystalline 0.1 to 1.0 %  
7631-86-9 Silica, Amorphous 0.1 to 1.0 %

85-68-7 Butyl Benzyl Phthalate 1 to 5 %  
 100-41-4 Ethylbenzene 1 to 5 %  
 78-93-3 Methyl Ethyl Ketone 5 to 10 %  
 108-88-3 Toluene 20 to 30 %



**TSCA:** The following are not listed under TSCA:

-None

**SARA:** The following are reportable under SARA

78-93-3 Methyl Ethyl Ketone 5 - 10%  
 Acrylic Polymer, Proprietary (non hazardous) 5 - 10%  
 100-41-4 Ethylbenzene 1.0 - 5%  
 1330-20-7 Xylene 5 - 10%  
 85-68-7 Butyl Benzyl Phthalate 1.0 - 5%  
 108-88-3 Toluene 20 - 30%  
 66402-68-4 Anhydrous Aluminum Silicate 1.0 - 5%  
 7631-86-9 Silica, Amorphous 0.1 - 1.0%

**Section 16 - Other Information**


Note: HMIS Ratings involve data and interpretations that can vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

**Hazardous Material Information System (HMIS)**

<b>HEALTH</b>	<input type="text" value="3"/>
<b>FLAMMABILITY</b>	<input type="text" value="3"/>
<b>PHYSICAL HAZARD</b>	<input type="text" value="0"/>
<b>PERSONAL PROTECTION</b>	<input type="text"/>

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH

**National Fire Protection Association (NFPA)**



Date Prepared: 2/5/2015

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.