

SAFETY DATA SHEET

Section 1 - Product and Company Identification

Product Name: 2K Epoxy Primer/Sealer - Black
Manufacturer/Supplier:
TRANSTAR AUTOBODY TECHNOLOGIES
2040 Heiserman Dr.
Brighton, MI, 48114, USA

Product Code: 6161, 6164
24 Hour Emergency Phone(s):
USA 800-424-9300 (CHEMTREC)
International 001-703-527-3887 (CHEMTREC Int'l)

Business Phone: 810-360-1600
SDS Prepared By: Transtar Autobody Technologies

Product Use: For Professional and Industrial Use Only
Not recommended for: Not for sale to the general public

Section 2 - Hazards Identification

Classification of the substance or mixture

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Carcinogen	2	Limited evidence of human or animal carcinogenicity
Reproductive toxin	2	Human or animal evidence possibly with other information
Organ toxin single exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance) - Human evidence in exceptional cases
Organ toxin repeated exposure	1	Significant toxicity in humans; Reliable, good quality human case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure
Aquatic toxicity	A2	Acute toxicity > 1.00 but <= 10.0 mg/l

GHS Hazards

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H371	May cause damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life

GHS Precautions

P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking
P233	Keep container tightly closed
P240	Ground and bond container and receiving equipment

P241	Use explosion-proof electrical, ventilating, lighting and motorized equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust, mist, vapors or spray
P264	Wash contacted skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves, protective clothing, eye protection, face protection and respiratory protection.
P303+P361+P353	IF ON SKIN (or hair): Immediately take off all contaminated clothing. Wash skin with soap and water.
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice
P337+P313	If eye irritation persists: Get medical advice.
P370+P378	In case of fire: Use dry chemical, CO ₂ , foam or water fog to extinguish
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents and container in accordance with local, regional, national and international regulations.

Danger



Hazards not otherwise classified (HNOC) or not covered by GHS:

None known

Section 3 - Composition

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Calcium Carbonate 1317-65-3 20 to 30%	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	ACGIH has set a TWA of 10 mg/m ³ (for dust containing no asbestos and <1% free silica).	NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)

Polymer of epoxy resin and bisphenol A 25036-25-3 10 to 20%			
Barium Sulfate 7727-43-7 10 to 20%	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	5 mg/m3 TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Acetone 67-64-1 10 to 20%	1000 ppm TWA; 2400 mg/m3 TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m3 TWA
Ethyl-3-ethoxypropionate 763-69-9 5 to 10%	TWA: 0.75 ppm	CLV: 0.03 ppm	
Xylene 1330-20-7 5 to 10%	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	
Natural wollastonite 13983-17-0 1 to 5%	As particles not otherwise regulated (PNOR). OSHA PEL: TWA respirable fraction formula: 10 mg/m3 / % SiO2 +2 TWA: 15 mg/m3 total dust 5 mg/m3 respirable dust (OSHA)	ACGIH: TWA 0.025 mg/m3 from respirable fraction	
Ethylene glycol monobutyl ether acetate 112-07-2 3.0 percent		20 ppm TWA	NIOSH: 5 ppm TWA; 33 mg/m3 TWA
Propylene Glycol Monomethyl Ether 107-98-2 2.7 percent	There is no OSHA PEL.	100 ppm STEL 50 ppm TWA	NIOSH: 100 ppm TWA; 360 mg/m3 TWA 150 ppm STEL; 540 mg/m3 STEL
Ethylbenzene 100-41-4 1 to 5%	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
Isopropyl Alcohol 67-63-0 1 to 5%	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
Castor oil, polymer with Bisphenol A and Epichlorohydrin epoxy ester 68513-59-7 1 to 5%			
Carbon Black 1333-86-4 0.1 to 1.0%	3.5 mg/m3 TWA	3 mg/m3 TWA (inhalable fraction)	NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

Section 4 - First Aid Measures

INHALATION: If Inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing difficulty persists, seek medical attention.

EYE CONTACT: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for a minimum of 15 minutes while holding eye lids open. If eye irritation persists: seek medical attention.

SKIN CONTACT: Take off all contaminated clothing immediately. Wash exposed area thoroughly with soap and water. Seek medical attention if irritation persists. Do NOT use solvents or thinners to wash off.

INGESTION: If swallowed, seek medical attention immediately and have product container or label at hand. DO NOT INDUCE VOMITING unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed:

Dizziness, breathing difficulty, headaches, & loss of coordination .

Indication of any immediate medical attention and special treatment needed.

Seek professional medical attention for all over-exposures and/or persistent problems.

Section 5 - Fire Fighting Measures

LEL: 0.9 %

UEL: 22.7 %

Extinguishing Media: Dry Chemical, Foam, CO2 or water fog.

Unsuitable Extinguishing Media: High volume water jets

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back . Closed containers may explode when exposed to extreme heat or burst when contaminated with water (CO2 gas evolved). Hazards apply to empty containers. Combustion generates toxic fumes.

Hazardous Combustion Products: oxides of carbon, oxides of nitrogen, formaldehyde, toxic fume

Special Firefighting Procedures: Highly toxic fumes may be generated by thermal decomposition. Water runoff from firefighting can cause environmental damage. Dike and collect water used to fight fire.

Fire Equipment: Full fire fighter equipment including SCBA should be worn to avoid skin contact and inhalation of concentrated vapors. Minimize skin exposure.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Avoid breathing vapors and mist. Ensure adequate ventilation. Eliminate all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulation to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up:

Dike spill area and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Sweep up and dispose of in appropriate containers in accordance to Federal, State and/or Local regulations. Clean preferably with a detergent; avoid use of solvents.

Section 7 - Handling and Storage

Safe Handling Measures: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Ground and bond container and receiving equipment. Use non-sparking tools and explosion proof equipment when handling this material. Keep away from sources of ignition - No Smoking. Use in cool, well-ventilated areas. Keep containers closed when not in use. Take measures to prevent the build up of electrostatic charge. Follow all SDS and label precautions even after container is emptied because they may retain product residues. For precautions see section 2.

Storage Requirements: Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces-No Smoking. Store in a cool, dry and well-ventilated place. Do not reuse container when empty.

Section 8 - Exposure Control and PPE

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Calcium Carbonate 1317-65-3	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	ACGIH has set a TWA of 10 mg/m ³ (for dust containing no asbestos and <1% free silica).	NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)
Polymer of epoxy resin and bisphenol A 25036-25-3			
Barium Sulfate 7727-43-7	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	5 mg/m ³ TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica)	NIOSH: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m ³ TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m ³ TWA
Ethyl-3-ethoxypropionate 763-69-9	TWA: 0.75 ppm	CLV: 0.03 ppm	
Xylene 1330-20-7	100 ppm TWA; 435 mg/m ³ TWA	150 ppm STEL 100 ppm TWA	
Natural wollastonite 13983-17-0	As particles not otherwise regulated (PNOR). OSHA PEL: TWA respirable fraction formula: 10 mg/m ³ / % SiO ₂ +2 TWA: 15 mg/m ³ total dust 5 mg/m ³ respirable dust (OSHA)	ACGIH: TWA 0.025 mg/m ³ from respirable fraction	
Ethylene glycol monobutyl ether acetate 112-07-2		20 ppm TWA	NIOSH: 5 ppm TWA; 33 mg/m ³ TWA
Propylene Glycol Monomethyl Ether 107-98-2	There is no OSHA PEL.	100 ppm STEL 50 ppm TWA	NIOSH: 100 ppm TWA; 360 mg/m ³ TWA 150 ppm STEL; 540 mg/m ³ STEL
Ethylbenzene 100-41-4	100 ppm TWA; 435 mg/m ³ TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m ³ TWA 125 ppm STEL; 545 mg/m ³ STEL

Isopropyl Alcohol 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
Castor oil, polymer with Bisphenol A and Epichlorohydrin epoxy ester 68513-59-7			
Carbon Black 1333-86-4	3.5 mg/m3 TWA	3 mg/m3 TWA (inhalable fraction)	NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

Engineering Controls: Ground and bond container and receiving equipment. Use explosion proof electrical, ventilation, lighting and motorized equipment. Use non-sparking tools. Ensure adequate ventilation.

Ventilation: General mechanical ventilation or local exhaust should be utilized to keep vapor concentrations below exposure limits (PEL & TLV). Ventilation equipment must be explosion proof.

Safe Work Practices: Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands thoroughly after using and before eating, drinking or smoking. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used. Spraying of material can cause an oxygen deficient environment. Use proper ventilation to remove vapors, mist and fumes combined with NIOSH approved respirator.

Respiratory Protection: When working with this material use a MSHA/NIOSH approved cartridge respirator or suitable respiratory protection to keep airborne mists and vapor concentrations below the PEL & TLV limits. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

Eye/Face Protection: Use safety glasses with chemical splash goggles or faceshield.

Skin Protection: Use chemical resistant gloves.

Body Protection: Impervious clothing, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Contaminated Gear: Take off contaminated clothing immediately and wash before reuse.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<p>Appearance Black</p> <p>Odor Organic Solvent</p> <p>pH: No data available</p> <p>Freezing point: No data available</p> <p>Flash point: -4 F, -20 C</p> <p>Flammability: No data available</p> <p>Vapor Pressure: 66.7 mmHg</p> <p>Density (Lb / Gal) 11.40</p> <p>Partition coefficient (n-octanol/water): No data available</p>	<p>Physical State Liquid</p> <p>Odor threshold: No data available</p> <p>Melting point: No data available</p> <p>Boiling range: 56°C</p> <p>Evaporation rate: No data available</p> <p>Explosive Limits: 1% - 23%</p> <p>Vapor Density: 3.5</p> <p>Solubility: No data available</p> <p>Autoignition temperature: 280°C</p>
--	--

Decomposition temperature: No data available Regulatory Coating VOC g/L 401 Actual Coating VOC g/L 321 Weight Percent Volatile 35.13 % Weight VOC 23.51 % Wt Exempt VOC 11.62	Viscosity: No data available Regulatory Coating VOC 3.35 lb/gal Actual Coating VOC lb/Gal 2.68 Specific Gravity (SG) 1.366 % Weight Water 0.0 % Vol Exempt VOC 20.04
--	---

Section 10 - Stability and Reactivity

Reactivity: No data available

Stability: Stable under recommended storage conditions.

Possibility of hazardous reactions: Vapors may form explosive mixture with air. Hazardous polymerization will not occur.

Conditions to avoid: Heat, flame and sparks. Extreme temperature and direct sunlight.

Incompatible with:

- Strong oxidizing agents
- Strong oxidizers
- Acids

Hazardous products produced under decomposition:

Carbon Monoxide, Carbon Dioxide.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity: 177mg/L

Component Toxicity

1330-20-7	Xylene Oral: 3,500 mg/kg (Rat) Dermal: 4,350 mg/kg (Rabbit) Inhalation: 29 mg/L (Rat)
112-07-2	Ethylene glycol monobutyl ether acetate Oral: 3,000 mg/kg (Rat) Dermal: 1,480 mg/kg (Rabbit)
107-98-2	Propylene Glycol Monomethyl Ether Oral: 5,000 mg/kg (Rat) Dermal: 13 g/kg (Rabbit)
100-41-4	Ethylbenzene Oral: 3,500 mg/kg (Rat) Inhalation: 17 mg/L (Rat)
67-63-0	Isopropyl Alcohol Oral: 1,870 mg/kg (Rat) Dermal: 4,059 mg/kg (Rabbit)

This mixture has not been tested for toxicological effects.

Acute Effects:

- INHALATION - Dizziness, breathing difficulty, headaches, & loss of coordination.
- EYE CONTACT - Moderate irritation, tearing, redness, and blurred vision.
- SKIN CONTACT - Moderate irritant. Can dry and defat skin causing cracks, irritation, and dermatitis.
- INGESTION - Can cause gastrointestinal irritation, vomiting, nausea, & diarrhea.

Chronic Effects:

May affect liver, kidney and central nervous system with repeated exposure. Prolonged or repeated exposure may

cause lung injury.

Routes of Entry

Inhalation

Skin Contact

Eye Contact

Ingestion

Target Organs

**Blood System
Eyes
Skin**

**Kidneys
Liver
Respiratory System**

Lungs

Central Nervous System

Reproductive

Effects of Overexposure

Short Term Exposure

Contact can irritate the skin. Exposure can irritate the eyes and respiratory tract. Exposure to high concentrations can cause dizziness, lightheadedness, and unconsciousness. Propylene glycol monomethyl ether can affect you when breathed in and by passing through your skin. Contact can irritate the eyes and skin. Exposure can irritate the nose and throat. Very high levels may cause lung, liver, and kidney damage. Very high levels of propylene glycol monomethyl ether may cause central nervous system depression; dizziness and lightheadedness, and unconsciousness. Inhalation may cause irritation to respiratory tract. Skin contact may cause irritation. Eye contact may cause irritation. Inhalation: Exposure to vapor can be irritation to the nose and throat. Inhalation of vapor at concentrations above 200 ppm or 3 - 5 minutes can lead to xylene intoxication. Symptoms include headache, dizziness, nausea and vomiting. If exposure should continue, central nervous system depression characterized by shallow breathing and weak pulse can occur. Levels of 230 ppm for 15 minutes may cause lightheadedness without loss of equilibrium. Reversible liver and kidney damage in man has followed exposure to sudden high concentrations of vapor. Such high levels may also give rise to lung congestion. Exposure to extremely high concentrations (10,000 ppm or more) of xylene vapors can lead to a strong narcotic effect with symptoms of slurred speech, stupor fatigue, confusion, unconsciousness, coma, and possible death. Ethyl benzene irritates the eyes, skin, and respiratory tract. Exposure to high concentrations can cause dizziness, lightheadedness and unconsciousness. Very high exposures (above the OEL) can cause difficult breathing, narcosis, coma, and even death. Swallowing the liquid may cause aspiration into the lungs, resulting in chemical pneumonitis. May affect the central nervous system. Concentration of 200 ppm can cause irritation.

Long Term Exposure

Repeated skin exposure can cause dryness and skin cracking. This chemical has not been adequately evaluated to determine whether brain or nerve damage could occur with repeated exposure. However, many solvents and other petroleum-based chemicals have been shown to cause such damage. Effects may include reduced memory and concentration, personality changes (withdrawal, irritability), and fatigue, sleep disturbances, reduced coordination, and/or effects on the nerves to the arms and legs (weakness, "pins and needles"). Causes skin dryness; dermatitis. May cause liver and kidney damage. Can irritate the lungs; bronchitis may develop. Exposure to levels well above 3.5 mg/m3 for several months may result in damage to the skin and nails, temporary or permanent damage to the lungs and breathing passages, and adversely affect the heart. Carbon Black containing PAH greater than 0.1% should be considered a suspect carcinogen. Lungs may be affected by repeated or prolonged exposure at very high concentrations: Some Carbon blacks may contain compounds which are carcinogenic and as organic extracts of these have been classified as possibly carcinogenic to humans, special care should be taken to avoid exposure to such extracts. Lung effects remain controversial and may be due to contaminants. It is probable that minor effects reported are non-specific effects associated with exposure to nuisance dusts in general. Polyaromatic hydrocarbons (PAH) are reportedly present in some carbon blacks. Depending on the process of manufacture, there are variations in their chemical compositions. Inhalation of xylene vapor and skin contact with liquid are the two most probable routes of long term exposure. Symptoms of inhalation are dizziness, headache and nausea. Long term exposure has been associated with liver and kidney damage, intestinal tract disturbances and central nervous system depression. Prolonged contact with skin can lead to irritation, dryness and cracking. Repeated exposure can cause poor memory, difficulty in concentration, and other brain effects. It can also cause damage to the eye surface. Repeated or prolonged exposure to the skin may cause drying, scaling and blistering. May cause kidney disease, liver disease, chronic respiratory disease, skin disease, as follows: EB is not nephrotoxic. Concern is expressed because the kidney is the primary route of excretion of EB and its metabolites. EB is not hepatotoxic. Since EB is metabolized by the liver, concern is expressed for these tissues. Exacerbation of pulmonary pathology might occur following exposure to EB. Individuals with impaired pulmonary function might be at risk. EB is a defating agent and may cause dermatitis following prolonged exposure. Individuals with preexisting skin problems may be more sensitive to EB. There is limited evidence that EB may damage the developing fetus, and may cause mutations.

The following chemicals comprise of at least 0.1% of this mixture and are listed and/or classified as carcinogens or potential carcinogens by the NTP, IARC, OSHA (mandatory listing) or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
1333-86-4	Carbon Black	0.1 to 1.0%	Carbon Black: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
100-41-4	Ethylbenzene	1 to 5%	Ethylbenzene: IARC: Possible human carcinogen OSHA: listed

Section 12 - Ecological Information

This material has not been tested for ecological effects.

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects: Contains photochemically reactive solvent.

Component Ecotoxicity

Acetone	96 Hr LC50 <i>Oncorhynchus mykiss</i> : 4.74 - 6.33 mL/L; 96 Hr LC50 <i>Pimephales promelas</i> : 6210 - 8120 mg/L [static]; 96 Hr LC50 <i>Lepomis macrochirus</i> : 8300 mg/L 48 Hr EC50 <i>Daphnia magna</i> : 10294 - 17704 mg/L [Static]; 48 Hr EC50 <i>Daphnia magna</i> : 12600 - 12700 mg/L
Ethyl-3-ethoxypropionate	96 Hr LC50 <i>Pimephales promelas</i> : 62 mg/L [static] 48 Hr EC50 <i>Daphnia magna</i> : 970 mg/L
Xylene	96 Hr LC50 <i>Pimephales promelas</i> : 13.4 mg/L [flow-through]; 96 Hr LC50 <i>Oncorhynchus mykiss</i> : 2.661 - 4.093 mg/L [static]; 96 Hr LC50 <i>Oncorhynchus mykiss</i> : 13.5 - 17.3 mg/L; 96 Hr LC50 <i>Lepomis macrochirus</i> : 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 <i>Lepomis macrochirus</i> : 19 mg/L; 96 Hr LC50 <i>Lepomis macrochirus</i> : 7.711 - 9.591 mg/L [static]; 96 Hr LC50 <i>Pimephales promelas</i> : 23.53 - 29.97 mg/L [static]; 96 Hr LC50 <i>Cyprinus carpio</i> : 780 mg/L [semi-static]; 96 Hr LC50 <i>Cyprinus carpio</i> : >780 mg/L; 96 Hr LC50 <i>Poecilia reticulata</i> : 30.26 - 40.75 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 <i>Gammarus lacustris</i> : 0.6 mg/L
Ethylene glycol monobutyl ether acetate	48 Hr EC50 <i>Daphnia magna</i> : 37 mg/L 72 Hr EC50 <i>Desmodesmus subspicatus</i> : >500 mg/L
Propylene Glycol Monomethyl Ether	96 Hr LC50 <i>Pimephales promelas</i> : 20.8 g/L [static] 48 Hr EC50 <i>Daphnia magna</i> : 23300 mg/L
Ethylbenzene	96 Hr LC50 <i>Oncorhynchus mykiss</i> : 11.0 - 18.0 mg/L [static]; 96 Hr LC50 <i>Oncorhynchus mykiss</i> : 4.2 mg/L [semi-static]; 96 Hr LC50 <i>Pimephales promelas</i> : 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 <i>Lepomis macrochirus</i> : 32 mg/L [static]; 96 Hr LC50 <i>Pimephales promelas</i> : 9.1 - 15.6 mg/L [static]; 96 Hr LC50 <i>Poecilia reticulata</i> : 9.6 mg/L [static] 48 Hr EC50 <i>Daphnia magna</i> : 1.8 - 2.4 mg/L 72 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : 4.6 mg/L; 96 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : >438 mg/L; 72 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : 2.6 - 11.3 mg/L [static]; 96 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : 1.7 - 7.6 mg/L [static]
Isopropyl Alcohol	96 Hr LC50 <i>Pimephales promelas</i> : 9640 mg/L [flow-through]; 96 Hr LC50 <i>Pimephales promelas</i> : 11130 mg/L [static]; 96 Hr LC50 <i>Lepomis macrochirus</i> : >1400000 µg/L 48 Hr EC50 <i>Daphnia magna</i> : 13299 mg/L 96 Hr EC50 <i>Desmodesmus subspicatus</i> : >1000 mg/L; 72 Hr EC50 <i>Desmodesmus subspicatus</i> : >1000 mg/L

Section 13 - Disposal Considerations

Product should be disposed of in accordance with all Federal, State and local regulations. Contact a licensed professional waste disposal service to dispose of this material. Subject to hazardous waste generation, treatment, storage and disposal rules under RCRA, 40CFR261.

Section 14 - Transportation Information

The following transportation information is provided based on Transtar Autobody Technologies interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
IMDG	Paint	UN1263	II	3
IATA	Paint	UN1263	II	3
USDOT	Paint	UN1263	II	3

For inner packagings not exceeding 5L each packaged in a strong outer box: Limited Quantity

Section 15 - Regulatory Information

The information listed in this section is not all inclusive of all regulations for this product or the chemical components of this product.

California Hazardous Substance List:

- None

HAPS: This formulation contains the following HAPS:

100-41-4 Ethylbenzene 1 to 5 %
1330-20-7 Xylene 5 to 10 %

NJ RTK: The following chemicals are listed under New Jersey RTK

1333-86-4 Carbon Black 0.1 to 1.0 %
67-63-0 Isopropyl Alcohol 1 to 5 %
100-41-4 Ethylbenzene 1 to 5 %
107-98-2 Propylene Glycol Monomethyl Ether 2.7 %
112-07-2 Ethylene glycol monobutyl ether acetate 3.0 %
1330-20-7 Xylene 5 to 10 %
67-64-1 Acetone 10 to 20 %
7727-43-7 Barium Sulfate 10 to 20 %
1317-65-3 Calcium Carbonate 20 to 30 %

California Proposition 65

WARNING: This product contains the following chemical(s) known to the State of California to cause birth defects or other reproductive harm.

107-98-2 Propylene Glycol Monomethyl Ether 2.7 %

California Proposition 65

WARNING: This product contains the following chemical(s) known to the State of California to cause cancer .

1333-86-4 Carbon Black 0.1 to 1.0 %
100-41-4 Ethylbenzene 1 to 5 %

PA RTK: The following chemicals are listed under Pennsylvania RTK:

1333-86-4 Carbon Black 0.1 to 1.0 %
67-63-0 Isopropyl Alcohol 1 to 5 %
100-41-4 Ethylbenzene 1 to 5 %
107-98-2 Propylene Glycol Monomethyl Ether 2.7 %
1330-20-7 Xylene 5 to 10 %
67-64-1 Acetone 10 to 20 %
7727-43-7 Barium Sulfate 10 to 20 %
1317-65-3 Calcium Carbonate 20 to 30 %

EU REACH SIN: The chemicals listed below are on the EU REACH SIN list

- None

SARA 312: This Product contains the following chemicals subject to the reporting requirements of SARA 312:

100-41-4 Ethylbenzene 1 to 5 %

SARA 313: This Product contains the following chemicals subject to the reporting requirements of SARA 313:

100-41-4 Ethylbenzene 1 to 5 %

WHMIS:

- 1333-86-4 Carbon Black 0.1 to 1.0 %
- 67-63-0 Isopropyl Alcohol 1 to 5 %
- 100-41-4 Ethylbenzene 1 to 5 %
- 107-98-2 Propylene Glycol Monomethyl Ether 2.7 %
- 67-64-1 Acetone 10 to 20 %



TSCA: The following are not listed under TSCA:None

SARA: The following are reportable under SARA

- 107-98-2 Propylene Glycol Monomethyl Ether 2.7%
- 67-63-0 Isopropyl Alcohol 1.0 - 5%
- 112-07-2 Ethylene glycol monobutyl ether acetate 3.0%
- Acrylic Polymer, Proprietary (non hazardous) 1.0 - 5%
- 1330-20-7 Xylene 5 - 10%
- 111-76-2 n-Butoxyethanol 0.1 - 1.0%
- 100-41-4 Ethylbenzene 1.0 - 5%

Section 16 - Other Information


Note: HMIS Ratings involve data and interpretations that can vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	<input type="text"/>

HMIS & NFPA Hazard Rating Legend
 * = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



Date Prepared: 1/28/2015

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Transtar Autobody Technologies to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.